



PATENT ABSTRACTS OF JAPAN

(11) Publication number: 08247301 A

(43) Date of publication of application: 27.09.1996

(51) Int. Cl F16K 1/36

F16K 1/42, F16K 7/17, F16K 31/128

(21) Application number: 08028154

(22) Date of filing: 15.02.1996

(30) Priority: 15.02.1995 CH 95 439

(71) Applicant: GEORG FISCHER
ROHRLEITUNGSSYST AG(72) Inventor: SCHALK ADELBERT
GREITMANN RALF

(54) VALVE

and tight sealing in a valve can be secured by a ring-shaped sealing face 58 based on the diaphragm 36.

(57) Abstract:

PROBLEM TO BE SOLVED: To provide a valve having a movable face making no direct contact with a flow medium so as to secure a maximum valve operation efficiency even when using an irritable medium.

SOLUTION: In a channel 16 of a housing 10, a diaphragm 36 seals a cylindrical chamber 48 from a medium inside the channel 16, while a disc 44 arranged in one end of a sleeve 40 divides the cylindrical chamber 48 into small chambers 50, 52. According to a shift of the sleeve 40, the other end face 42 is forcibly pressed to a guiding face 34 in a flow main body 18,

COPYRIGHT: (C)1996,JPO

